

Signen Gateway ¹	Home SP 12K	Home TP 30K	Units
Grid Connection			
Grid connection type	Single phase	Three phase	
Nominal AC input / output voltage	220 / 230 / 240	380 / 400	V
Nominal AC input / output current	52.2	45.6	A
Nominal AC input / output power	12 / 12.6 / 13.2	30	kW
Nominal AC frequency	50 / 60		Hz
Disruption time of backup switch ²	0		ms
AC Output to Backup Port			
Nominal AC output voltage	220 / 230 / 240	380 / 400	V
Nominal AC output current	52.2	45.6	A
Nominal AC output power	12 / 12.6 / 13.2	30	kW
Nominal AC frequency	50 / 60		Hz
Overvoltage category	III		
AC Output to Non-Backup Port			
Nominal AC output voltage	220 / 230 / 240	380 / 400	V
Nominal AC output current	52.2	45.6	A
Nominal AC output power	12 / 12.6 / 13.2	30	kW
Nominal AC frequency	50 / 60		Hz
Inverter Connection			
Nominal AC voltage	220 / 230 / 240	380 / 400	V
Nominal AC input current	52.2 (INV1), 32 (INV2) ³	45.6	A
General Data			
Dimensions (W / H / D)	495 / 370 / 167		mm
Weight	12.5	13.5	kg
Storage temperature range	-40 ~ 70		°C
Operating temperature range	-30 ~ 55		°C
Relative humidity range	0% ~ 95%		
Max. operation altitude	4000		m
Cooling	Natural convection		
Ingress protection rating	IP54		
Communication	Fast Ethernet , dry contact		
Installation method	Wall mounted		

1. Please contact Sigenergy or local distributors for specific countries where sales are available.
2. This refers to the load-side disruption time, to achieve this functionality Sigen Energy Gateway needs to be used together with Sigen Energy Controller and Sigen Battery. Test conditions: In the open-circuit state of the power grid, the nominal power of the Sigen Energy Controller is higher than the total power of the backup loads.
3. For Sigenergy single phase inverter products, 8.0-12.0 kW inverters should be connected to the INV1 port, 3.0-6.0 kW inverters should be connected to the INV2 port. Only one inverter can be connected to the Gateway.